



SNS PoE Digital Clocks



The Power over Ethernet Advantage

SNS™ PoE digital clocks utilize Power over Ethernet (PoE), the same technology that powers IP phones. PoE is a network standard based on IEEE 802.3af that delivers DC power to Ethernet connected devices. PoE eliminates the need for wall transformers, allows centralized UPS backup, and is fully compatible with powered and non-powered 10/100BaseT Ethernet devices. PoE can be enabled on an existing network by placing simple midspan solutions (available from most network equipment vendors) in a switch room or at an endpoint.

The power over ethernet digital clocks provide synchronized time throughout a facility in a system that's easy to install and manage. These innovative clocks plug directly into a standard Ethernet jack, drawing both time updates and power over the network. No AC outlets are needed — eliminating cost and complexity from system deployment.

Features

- Visible at over 150 feet with 4-inch red and green LEDs. numerals
- Synchronized time without the cost of installing AC outlets
- Time is automatically set by Network Time Protocol (NTP)
- Use your existing Ethernet LAN and the same network components as IP phones
- Manage all PoE clocks in the SNS AMP software

	4-Digit	6-Digit
Molded Plastic — Black	SNS5X201BP	—
Molded Plastic — Putty	SNS5X201PP	—
Molded Plastic — Off-White	SNS5X2010WP	—
Brushed Stainless Steel	SNS5X201SS	SNS5X203SS
Aluminum — Black	SNS5X201BA	SNS5X203BA
Flush Mounted	SNS5X201FBM	SNS5X203FBM
Pendant/Cantilever Mounting Kit	SNS4KIT	SNS6KIT

- Add a "G" after the item number for green LED models
Example: SNS5X201BPG


Physical Specifications

4-Digit Models - 4-Digit, Red or Green 7-Segment LEDs

- Dimensions: 12"L x 6"H x 2.2"D (30cm x 15cm x 5.6cm)
- Cabinets: Plastic or Aluminum in Black, Putty or Off-White, Brushed Stainless Steel
- Weight:
 - Painted Cabinet: 2 lbs.
 - Stainless Cabinet: 3.75 lbs. (1.7kg)

Cabinet Colors:


Black
Pantone 426 C



Putty
Pantone 7500 U



Off-White
Pantone Gray 2 C



6-Digit Models - 6-Digit, Red or green 7-Segment LEDs

- Dimensions: 17.5"L x 6"H x 2.2"D (44.5cm x 15cm x 5.6cm)
- Cabinets: Plastic or Aluminum in Black, Putty or Off-White, Brushed Stainless Steel
- Weight:
 - Painted Cabinet: 2.5 lbs. (1.1 kg)
 - Stainless Cabinet: 5 lbs. (2.3 kg)

Technical Specifications

- Viewing Distance: 150+ feet (50+ meters)
- Accuracy: +/- approximately 200 milliseconds
- Operating Temperature: 32° to 104° F (0° to 40° C)
- Operating Humidity: 95% maximum, non-condensing
- Mounting Options: Surface, Pendant, Cantilever, Flush Inset, Double Sided
- Certifications: UL 1950, ETL Listed, CE Marked, RoHS Compliant

Mounting Options


Surface Mount

SNS PoE digital clocks have two keyhole slots on the rear of the clock for surface mounting. The clock back includes a recess for mounting over an Ethernet receptacle



Pendant/Cantilever

With an optional mounting kit you can hang the clocks from the ceiling or wall, allowing greater visibility in areas like hallways. You can also piggyback two clocks, so time is visible in both directions.



Flush Mount

A separate flush mount model allows you to inset the clock into a wall, creating a more finished look. Available in 4-digit and 6-digit models that come complete with trim in black metal.

