

September, 2009

1 Primex Wireless, Inc.  
2 1310 Kerrisdale Blvd. Unit #4  
3 Newmarket, ON L3Y 8V6  
4 800-330-1459  
5 www.primexwireless.ca  
6  
7

## 8 **Product Guide Specification**

9  
10 **Specifier Note: This product specification is written according to the Construction**  
11 **Specifications Institute (CSI), *MasterFormat™*, *SectionFormat*, and *PageFormat*,**  
12 **contained in the *CSI Manual of Practice*.**

13  
14 **The section must be carefully reviewed and edited by the**  
15 **Architect/Engineer/Consultant to meet the requirements of the project and local**  
16 **building code. Coordinate this section with other specification sections and the**  
17 **drawings.**

18  
19 **Delete all “Specifier Notes” when editing this section.**  
20

## 21 **DIVISION 27 53 13**

### 22 **XR WIRELESS CLOCK SYSTEMS**

23  
24 **Specifier Note: This section covers the Primex Wireless XR Synchronized Clock**  
25 **System. Consult Primex Wireless for assistance in editing this section for the**  
26 **specific application.**  
27

#### 28 29 **Part 1 General Requirements and Scope**

30 Furnish and install a complete new XR wireless clock system using Primex Wireless  
31 Inc. XR wireless system.

32 All bids shall be based on the equipment as specified herein. The specifying authority  
33 must approve any alternate system.

34  
35 (Reference Division 27 53 13 Clock Systems)

36 **Specifier Note: Edit the following list as required for the project.**  
37

#### 38 39 40 **1.1 Section Includes**

41 Transmission Systems GPS Receiver Primary Transmitter

42 Satellite Transmitter

43 Clocks

44 Analog

45 Digital  
46

**Specifier Note: Edit the following list as required for the project. List other sections with work directly related to this section.**

**1.2 Related Sections**

Division 26 00 00 – Electrical (120 volt grounded outlet required for transmitter.

Division 27 51 16 – Wireless Tone Generator

Division 27 42 10 – Digital Display Clocks and Timers

**Specifier Note: List standards referenced in this section, complete with designations and titles. This article does not require compliance with standards, but is merely a list of those used.**

**1.3 References**

This Technical Specification and Associated Drawings

Primex Wireless XR Satellite Time System User Manual.

**1.4 Definitions**

GPS: Global Positioning System, a worldwide system that employs 24 satellites in an integrated network to determine geographic location anywhere in the world, and which employs and transmits Universal Coordinated Time, the world’s most accurate and reliable time.

UTC: Universal Coordinated Time

NTP: Network Time Protocol, used for synchronizing the clocks on computer networks and devices from either a public server or a separate server on a private local area network.

**1.5 System Description**

XR wireless clock system shall continually synchronize clocks throughout the facility, and shall be capable of clock readouts in multiple time zones where desired.

The system shall provide wireless time from a master time source. This time source will either be the atomic clock on the GPS system or the clock from a defined NTP server that the XR transmitter can access via the customer Ethernet. The master time will be synchronized to UTC. Hard wiring will not be required to the clocks installed for the system. Clocks shall automatically adjust for Daylight Saving Time in locations where DST is observed.

Analog Clocks shall be synchronized to within 10 milliseconds 6 times per day, and

1 the system shall have an internal oscillator that maintains plus or minus one second per  
2 day between synchronizations, so that clock accuracy shall not exceed plus or minus  
3 0.2 seconds.

4  
5 The system shall include an internal clock reference so that failure to detect the master  
6 time source shall not result in the clocks failing to indicate time. Additionally, XR  
7 transmitters will have an internal battery backup of up to eight hours in the event of a  
8 power failure so that settings and the correct master time will be instantly recalled  
9 upon restoration of power.

10  
11  
12 The system shall incorporate a “fail-safe” design so that failure of any component shall  
13 not cause failure of the system. Upon restoration of power or repair of failed  
14 component, the system shall resume normal operation without the need to reset the  
15 system or any component thereof.

16  
17 Clock locations shall be as indicated, and clocks shall be fully portable, capable of  
18 being relocated at any time.

19  
20 The system must operate in accordance with a “Technical Acceptance Certificate”  
21 issued under the authority of Industry Canada and the Ministry of Industry. This  
22 license will be granted to and held by the end user.

## 23 24 **1.6 Regulatory Requirements**

25  
26 Equipment and components furnished shall be of manufacturer’s latest model.

27  
28 The end user will hold a license, known as a “Non Complex Fixed Station” Radio  
29 License granted by Industry Canada and the Ministry of Industry

30  
31 This license grants the end user protected use for wireless transmission at the  
32 designated frequency.

33  
34 IC-2365: Application for “License to Install and Operate a Radio Station in Canada”  
35 must be completed and signed by end user prior to license issuance. The end user will  
36 grant permission for Primex Wireless to apply for the license on their behalf. Primex  
37 Wireless will provide all documents and technical information to Industry Canada for  
38 approval.

39  
40 This license will designate a unique “call sign” for each end user.

41  
42 Transmitter and receiver shall comply with RSS 119 of Issue 6 of Industry Canada  
43 specifications as follows Equipment and components furnished shall be of  
44 manufacturer’s latest model.

45  
46 The end user will hold a license, known as a “Radio Station Authorization” granted by

1 the ICC.

2  
3 This license grants the end user protected use for wireless transmission at the  
4 designated frequency.

5  
6 This license will designate a unique “call sign” for each end user.

7  
8 Transmitter and receiver shall comply with RSS 119 of Issue 6 of Industry Canada  
9 specifications as follows:

10  
11 This device may not cause harmful interference, and

12  
13 This device must accept interference received, including interference that may cause  
14 undesired operation.

15  
16 Transmitter frequency shall be governed by IC: RSS119 Issue 6.

17  
18 Transmitter output power shall be governed by IC: RSS119 Issue 6

19  
20 System shall be installed in compliance with local and state authorities having  
21 jurisdiction.

## 22 23 **1.7 Submittals**

24  
25 Product Data: Submit complete catalog data for each component, describing physical  
26 characteristics and method of installation. Submit brochure showing available colors  
27 and finishes of clocks.

28  
29 **Specifier Note: In accordance with Industry Canada regulations, an**  
30 **application for “Technical Acceptance Certificate” must be filed prior to**  
31 **use of the equipment. Normally, the manufacturer will have completed**  
32 **the filing and obtaining the license. If not, the Owner will be required to**  
33 **file the application with the Industry Canada prior to use. Furnishing**  
34 **the license, or a copy of the application, will confirm that Industry**  
35 **Canada approval has been obtained.**  
36

37  
38 Operating License: Submit evidence of application for IC Radio Station Authorization  
39 prior to installing equipment. Furnish the license or a copy of the application for the  
40 license, to the Owner/End User prior to operating the equipment. The original license  
41 must be delivered to the Owner/End User.

42  
43 Samples: Submit one clock for approval. Approved sample shall be tagged and shall  
44 be installed in the work at location directed.  
45

1 Manufacturer's Instructions: Submit complete installation, set-up and maintenance  
2 instructions.

3

4 Floor plans indicating the location of system transmitter(s), approved by manufacturer,  
5 will be submitted to owner prior to installation.

6

7 **1.8 Substitutions**

8

9 Proposed substitutions, to be considered, shall be manufactured of equivalent materials  
10 that meet or exceed specified requirements of this Section.

11

12 Proposed substitutions shall be identified not less than 10 days prior to bid date.

13

14 Other systems requiring wiring and/or conduit between master and clocks will not be  
15 accepted.

16

17 Other systems using wireless technology in an unlicensed frequency range will not be  
18 accepted.

19

20 Other systems using wireless technology where the license is held by any party other  
21 than the end user will not be accepted.

22

23 **1.9 Quality Assurance**

24

25 Permits: Obtain operating license for the transmitter from the Industry Canada

26

27 Qualifications:

28

29 Manufacturer: Company specializing in manufacturing commercial time system  
30 products with a minimum of 30 continuous years of documented experience including  
31 4 years experience producing GPS wireless time systems.

32

33 Installer: Company with documented experience in the installation of commercial time  
34 systems.

35

36 Prior to installation, a site survey must be performed to determine proper transmitter  
37 placement.

38

39 **1.10 Delivery Storage and Handling**

40

41 Deliver all components to the site in the manufacturer's original packaging. Packaging  
42 shall contain manufacturer's name and address, product identification number, and  
43 other related information.

44

45 Store equipment in finished building, unopened containers until ready for installation.  
46

1  
2 **1.11 Project Site Conditions**  
3

4 Clocks shall not be installed until painting and other finish work in each room is  
5 complete.

6  
7 **Specifier Note: Delete following site condition if NTP will be the master time**  
8 **source:**  
9

10 Coordinate installation of GPS receiver for access to the roof or exterior side wall so  
11 that the bracket and related fasteners are watertight.

12  
13 **1.12 System Startup**  
14

15 At completion of installation and prior to final acceptance, turn on the equipment;  
16 ensure that all equipment is operating properly, and that all clocks are functioning.  
17

18 **1.13 Warranty**  
19

20 Manufacturer will provide a 1 year warranty on GPS receiver, transmitter, and satellite  
21 transmitter. All other components will have a 1 year warranty.  
22

23 **Part 2 – Products**  
24

25 **2.1 Manufacturer**  
26

27 XR wireless clock system shall be manufactured by Primex Wireless, Inc., 1310  
28 Kerrisdale Blvd., Unit 4, Newmarket ON L3Y 8V6, 800-330-1459  
29 www.primexwireless.ca.  
30

31 **2.2 Sequence of Operation**  
32

33 **Transmitter Operation**

34 When power is first applied to the transmitter, it checks for and displays the software  
35 version. It then checks the position of the switches and stores their position in  
36 memory. The transmitter looks for the master time source.  
37

38 **Specifier Note: Select procedure appropriate to the master time source from**  
39 **either of the following:**  
40

41  
42 **GPS Time Source**

43 With the XR transmitter in GPS mode, it powers a connected GPS engine mounted  
44 with a clear view of the sky. Upon power, the GPS module seeks the GPS satellites in  
45 orbit to determine position and UTC time. Once the transmitter acknowledges  
46 receivable GPS data, it downloads time data and synchronizes its internal master clock

1 to GPS time. The transmitter then starts to transmit its internal time once every  
2 second. The transmitter updates its internal clock every time it receives valid time  
3 data from the GPS.

4  
5 **NTP Time Source**

6 With the XR transmitter in NTP mode, it connects over the Ethernet to the IP address  
7 of the NTP server. This IP address is programmed into the transmitter as part of its  
8 configuration. Once the connection to the NTP server is acknowledged, it downloads  
9 time data and synchronizes its internal master clock to NTP time. The transmitter then  
10 starts to transmit its internal time once every second. The transmitter updates its  
11 internal clock in this mode once per hour.

12  
13  
14 **Analog Clock Operation**

15 Apply power or insert batteries. Follow set up procedures detailed in manufacturer's  
16 instructions.

17  
18 After initial setup, the clock will shut off the receiver. Six times each day, the  
19 microprocessor will activate the receiver and starting with the stored channel, it will  
20 again look for a valid time signal. If necessary, the clocks will resynchronize to the  
21 correct time.

22  
23 If the clock has not decoded a valid time signal for a pre-determined number of days, it  
24 will go to a step mode. Low battery voltage is a common cause of the clock to not  
25 properly decode a time signal. If a clock goes into step mode, replace the batteries  
26 first and then determine if the clock synchronizes to master time before attempting  
27 other troubleshooting methods.

28  
29 **2.3 Equipment**

30  
31 **General**

32 The clock system shall include a transmitter, indicating clocks, and all accessories for  
33 complete operation.

34  
35  
36 **Specifier Note: If NTP transmitter package is purchased, delete GPS Receiver  
37 statement, otherwise, select extension cable length, if applicable.**

38  
39 **GPS Receiver**

40 GPS roof mounted, with 10 foot cable (3m) attached  
41 Primex Wireless extension cable available: 50ft (15.25m), 100 ft (30.5m), and 200 ft  
42 (61m).

43  
44 The GPS Receiver shall be a complete GPS receiver including antenna in a waterproof  
45 case, designed for roof or outdoor mounting. Provide mounting bracket for attachment  
46 to roof structure.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46

The GPS Receiver cable must be plenum rated where required by local code.

**Transmitter:**

**Specifier Note: Select procedure appropriate to the master time source from either of the following:**

Primex Wireless Model **XR01IM**, consisting of wireless transmitter with GPS receiver, a surge suppressor/battery backup, and a mounting shelf. Unit shall obtain current atomic time from satellite. The clock system shall transmit time continuously to all clocks in the system.

Primex Wireless Model **XR01IN**, consisting of a wireless transmitter, surge suppressor/battery backup, and a mounting shelf. Unit shall obtain current NTP time from Ethernet network. The clock system shall transmit time continuously to all clocks in the system.

Transmission:

Frequency Ranges: 72.020 to 72.980 MHz, 74.610 to 74.790 MHz, 75.210 to 75.390 MHz, 75.440 to 75.600 MHz.

Transmission Power: 1 watt (30dBm) maximum

Radio technology: narrowband FM

Number of channels: 74

Channel bandwidth: 20 kHz maximum

Transition mode: one-way communication

Data rate: 2 KBps

Operating range: 32 degree F to 158 degrees F (0 degrees C. to 70 degrees C).

Transmitter:

Transmitter output power: +26 to +30 dBm

Frequency deviation: +/- 4 kHz

Transmitter power requirements: 120 VAC 60 Hz

Internal power requirements: 5 VDC

XR Wireless Clock Systems

Division 27 53 13

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46

Carrier frequency stability: +/- 20 ppm

Transmitter shall have 74 selectable channels to assure interference-free reception.

Transmitter shall have the following switches:

Time zone adjustment switches for all time zones in the world. Includes all Canadian time zones: Atlantic, Newfoundland, Eastern, Central, Mountain, and Pacific

DIP Switch to allow the following configuration: Daylight Saving Time bypass option, 12-hour or 24-hour display, GPS or NTP time source, Local or LAN configuration, UTC+ or UTC-, 30 minute UTC offset option (for Newfoundland).

Transmitter housing shall be black metal case, 16-3/4 inches (424.4mm) by 12 inches (304.8mm) by 1-7/8 inches (46.4mm) in size.

Antenna shall be 46 inches (1168mm) high, commercial type, mounted on top center of transmitter housing. Antenna gain shall be < 2.2 dB. Antenna polarization shall be vertical.

Transmitter housing shall incorporate a display which shall include the following:

Time readout

AM and PM indicator if 12-hour time display is set

Day and date readout

Time zone indicator including Standard or Daylight Savings Time

On screen menu to verify diagnostics, errors, time updates, and switch settings, toggled by sequence of push buttons next to display

Status LEDs: Green, which when solid indicates transmitter is broadcasting, yellow which flashes in the event of lack of time update after 48 hours, red which flashes to indicate connection or internal transmitter problem

Internal clock:

Transmitter shall contain an internal clock such that failure to update time from source will not disable the operation of the clocks.

Power supply (included)

Input: 120 volt AC 50/60 Hz, 0.4 amps.

Output: 9 volt DC, 1.5 amps.

Surge Protector/Battery Backup (included).

Input: 120 volt AC 60 Hz +/- 1 Hz.

XR Wireless Clock Systems

Division 27 53 13

1 Output: 120 volt AC, 500VA, 300 watts

2 Surge Energy Rating: 365 joules

3

4 Additional Equipment

5

6

**Specifier Note: Large buildings and multi-building projects may require satellite transmitters to provide proper coverage. Consult Primex Wireless for assistance in making this determination. If satellite transmitters are required, include the following two items in the project specification.**

7

8

9

10

11

Wireless Receiver Switches: Switches shall receive time packets from the Primary Transmitter and relay the synchronized time to the Satellite Transmitter connected to it. The unit shall include the following:

12

13

14

Antenna mounted on top of the switch housing, 11-1/2 inches (292mm) long.

15

16

Power Supply:

17

Input 120 VAC 50/60 Hz, 0.4 amps

18

Output: 9 volt DC, 1.5 amps

19

20

RS 232 data cable, 5 feet (1.5mm) long

21

22

Daylight Savings Time bypass switch

23

24

Dimensions: 4-1/4 inches (108mm) long, 5-3/4 inches (146mm) wide, 1-1/4 inches (31.75mm) deep.

25

26

27

Weight: 12 ounces (.34kg)

28

29

Operating Range: 32 degrees F to 158 degrees F (0 to 70 degrees C)

30

31

Satellite Transmitters Primex Wireless Model **XR01R**: Satellite Transmitters shall receive the signal from the Wireless Receiver Switches and transmit the signal to the devices in its vicinity, which are out of the range from the Master Transmitter. The unit shall include the following:

32

33

34

35

36

Antenna mounted on top of the housing, 46 inches (1168mm) long.

37

38

Wireless Receiver Switch.

39

40

Power Supply Input: 120 VAC, 50/60 Hz, 0.4 amps

41

Output: 9 volt DC, 1.5 amps.

42

43

6 foot (1.83m) cord

44

45

Surge Suppressor/Battery Backup

46

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45

Mounting Shelf.

Transmission Power: 1 watt maximum

72 MHz frequency.

Traditional analog clocks (battery): Analog clocks shall be wall mounted. Clocks shall have polycarbonate frame and polycarbonate lens. Face shall be white. Hour and minute hands shall be black.

- 9 inch (228.6mm) diameter analog clock: Primex Wireless Model **14280**
- 12-1/2 inch (317.5mm) diameter analog clock: Primex Wireless Model **14155**
- 16 inch (406.4mm) diameter analog clock: Primex Wireless Model **14163**
- 24 inch (610mm) diameter analog clock: Primex Wireless Model **14346**

Additional colors, finishes, and dial faces are available from manufacturer.

Analog clocks shall be battery-operated,

Analog clocks shall be capable of automatically adjusting for Daylight Saving Time. An on-off switch located on the transmitter shall disable this function if desired.

Time shall be automatically updated from the transmitter 6 times per day.

Analog clocks shall remember the time during changing of batteries.

9 inch (228.6mm) and 12.5 inch (317.5mm) analog clocks shall have a tamper proof/theft resistant clock lock mounting slots.

**Specifier Note: Select optional dial designs, colors, case options and hands from manufacturer's brochure**

Analog clock receivers shall be as follows:

Receiver sensitivity: >-110 dBm

Receiver power: dual lithium battery pack, supplied by manufacturer.

Antenna type: internal

Antenna gain: -7 dBd

XR Wireless Clock Systems

Division 27 53 13

1 If the transmitter stops transmitting valid time signals due to power failure, the clocks  
2 will continue to function as accurate quartz clocks until a valid time signal is decoded.  
3 If signal transmission is not restored after 96 hours, the second hand will “five step” as  
4 a visual indicator that the signal has been lost. Should the clocks lose power and  
5 signal, the clocks will not function.  
6

7 **Specifier Note: Analog clock faces can be made with Owner's logo as an option. If**  
8 **desired, leave in the following, and arrange for Owner to provide hard copy or**  
9 **digital copy of logo in format required by Primex Wireless. Contact Primex**  
10 **Wireless for details**  
11

12  
13 Traditional analog clocks (AC): Analog clocks shall be wall mounted. Clocks shall  
14 have polycarbonate frame and polycarbonate lens. Face shall be white. Hour and  
15 minute hands shall be black.  
16

17 12-1/2 inch (317.5mm) diameter analog clock, 24 VAC: Primex Wireless Model  
18 **14323** 12-1/2 inch (317.5mm) diameter analog clock, 120 VAC, Primex Wireless  
19 Model **14306**, Additional colors, finishes, and dial faces are available from  
20 manufacturer.  
21

22 Analog clocks shall be AC powered (24 VAC or 120 VAC). Clocks must have an 18  
23 inch (457.2mm) cord with 2 prong plug (120 VAC) or pigtail (24 VAC) to connect to  
24 power source.  
25

26 Analog clocks shall be capable of adjusting for Daylight Saving Time.  
27

28 Time shall be automatically be updated from the transmitter 6 times per day.  
29

30 If power is interrupted, the clock will stop until power resumes. Upon resumption of  
31 power, the clock will self correct to the current time.  
32

33 Clocks shall have a tamper proof/theft resistant clock lock mounting slots.  
34

35 Analog clock receivers shall be as follows:  
36

37 Receiver sensitivity: >-110 dBm  
38

39 Receiver power: 24 VAC or 120 VAC (see model #)  
40

41 Antenna type: internal  
42

43 Antenna gain: -7 dBd  
44

45 If transmitter stops transmitting valid time signals due to power failure, the clocks will  
46 continue to function as accurate quartz clocks until a valid time signal is decoded. If

1 signal transmission is not restored after 96 hours, the second hand will “five step” as a  
2 visual indicator that the signal has been lost. Should the clocks lose power and signal,  
3 the clocks will not function.  
4

5  
6 **Specifier Note: Analog clock faces can be made with Owner's logo as an option. If**  
7 **desired, leave in the following, and arrange for Owner to provide hard copy or**  
8 **digital copy of logo in format required by Primex Wireless. Contact Primex**  
9 **Wireless for details**

10  
11 Analog clock faces shall bear Owner’s logo as indicated.  
12

13 Digital Clocks: Primex Wireless Model **XRA1B203**, 6 digit -4 inch (101.6mm), 7  
14 segment red LED display.  
15

16 **Specifier Note:**  
17 **Select optional digit style, colors, and case styles from manufacturer’s brochure.**  
18

19  
20 Digital clocks must be able to receive synchronized time signal from Primex Wireless  
21 master or satellite transmitter.  
22

23 Digital clocks must have time and date option.  
24

25 Digital clocks shall be capable of automatically adjusting for Daylight Saving Time  
26

27 Power Supply: 120 VAC, 50-60 cycle.  
28

29 Digital clocks must be viewable from 150 feet (45.7m)  
30

31 **Specifier Note: Where desired for protection of clocks, specify the following**  
32 **optional equipment**  
33

34  
35 Wire guards: Provide one for each analog clock as follows:  
36

37 Analog clock wire guard Primex Wireless Model **14131**, 14 by 14 inch (355.6 by  
38 355.6 mm) size, for nominal 12-1/2 inch (317.5 mm) diameter analog clocks.  
39

40 Analog clock wire guard Primex Wireless Model **14123**, 18 by 18 inch (457.2 by  
41 457.2mm) size, for 16 inch (406.4mm) diameter analog clocks.  
42

43 Digital clock wire guard Primex Wireless Model **14388** for 2. 5 inch LED digital  
44 clocks  
45

46 Digital wire guard Primex Wireless Model 14389 for 4 inch LED digital clocks

1 Dual D Lithium Battery Pack Primex Wireless Model **14885** contains two sealed  
2 parallel lithium primary batteries.

3  
4 Cable Connection Sealant: Radio Shack Coaxial Cable Connector Sealant 278-1645,  
5 or approved electrical grade silicone sealant.  
6

7

### 8 **Part 3 – Execution**

9

#### 10 **3.1 Examination**

11

12 Verify that construction is complete in spaces to receive equipment and that rooms are  
13 clean and dry.

14

15 Verify that 120 volt electrical outlet is located within 6 feet (1.83m) of location of  
16 transmitter and the outlet is operational and properly grounded.  
17

17

#### 18 **3.2 Installation**

19

20 Provide all equipment necessary for a complete and operable system.

20

21

**Specifier Note – valid for transmitter with GPS input: The GPS unit can be mounted on the roof, on a pole, or at a window. In each case, the GPS unit must have a clear view of the sky. If the GPS unit is mounted on the roof, it must be located on a suitable bracket, well above the level of standing or incidental water. If the GPS unit is mounted at a window, it must be located away from low-E glass. If transmitter to use NTP as source, delete following work instruction with this note.**

22

23

24

25

26

27

28

29

30

31

32

33

34

35

36

37

38

39

40

41

42

43

44

45

46

**Specifier Note: Where desired for mounting transmitter, specify the following equipment: One Model Number 14005, 18 inches long, by 3 inches wide by 15 inches deep**

37 Transmitter:

39 Locate transmitter where indicated, a minimum of 2 to 3 feet (.6 to 1 meter) above the  
40 floor, away from large metal objects such as filing cabinets, lockers or metal framed  
41 walls. Transmitter(s) will be placed at locations indicated below:  
42

43

44

45

46

**Specifier Note: To assure optimum performance of the XR Wireless Clock System, transmitter(s) location (s) must be specified in the construction documents. Primex Wireless Applications Engineering Dept. should be consulted to determine the number and placement of transmitter(s) required for the project. Contact Primex Wireless Technical Support at 1-800-404-8117.**

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46

**Specifier Note: Select procedure appropriate to the master time source from either of the following:**

**If GPS Unit will be used as master time source**  
Attach GPS receiver to transmitter using cable. Set GPS/LAN DIP switch to GPS.

**If NTP will be used as master time source**  
Connect CAT5/CAT5e/CAT6 EIA/TIA standard Ethernet cable from transmitter LAN port to available network drop. Set GPS/LAN DIP switch to NTP.

**Specifier Note: If NTP is the master time source, the network drop used to connect the XR transmitter must have connectivity to the NTP server, which can be verified by the customer IT manager. The default NTP address is time.nist.gov. If the network has a different NTP IP address, it may be programmed into the transmitter by the installer to allow connection to the proper network time. Contact Primex Wireless Technical Support at 1-800-404-8117.**

- Connect antenna to transmitter, using care not to strip threads.
- Connect power supply to the transmitter.
- Connect power supply to the transmitter.  
Set the channel number on the display to correspond to the Industry Canada license.
- Plug power supply into electrical outlet.
- Analog clocks perform the following operations with each clock:
  - Set clock to correct time in accordance with manufacturer's instructions.
  - Observe analog clock until valid signals are received and analog clock adjusts itself to correct time.
  - Install the analog clock on the wall in the indicated location, plumb, level and tight against the wall. If using 12-1/2 inch (317.5mm) clock, attach using clock-lock hanging method and suitable fasteners as approved by clock manufacturer.
- Analog clocks (AC): Perform the following operations with each clock:
  - Observe clock until valid time signals are received and analog clock adjusts itself to correct time.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39

Install the analog clock on the wall in the indicated location, plumb, level, and tight against the wall. Attach using clock-lock hanging method and suitable fasteners as approved by clock manufacturer.

**Specifier Note: Delete the following if wire guards are not required**

Wire guards: Secure to wall, using approved theft-resistant fasteners.

**3.3 Adjusting**

Prior to final acceptance, inspect each clock, adjust as required, and replace parts which are found defective.

**3.4 Cleaning**

Prior to final acceptance, clean exposed surfaces of clocks, using cleaning methods recommended by clock manufacturer. Remove temporary labels from clock faces. Do not remove labels from backs of clocks.

**3.5 Demonstration**

Provide training to Owner's representative on setting and adjusting clocks, replacing batteries and routine maintenance.

**3.6 Protection**

Protect finished installation until final acceptance of the project.

**3.7 Testing**

All devices must be tested at their operational location under normal operational conditions to assure reception of signal.

**END OF SECTION**